

RECEIVED CENTRAL FAX CENTER

JAN 07 2008

PTO/SB/21 (04-07)

Approved for use through 09/30/2007. OMB 0851-0031


U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM (to be used for all correspondence after initial filing)	Application Number	09/751,785
	Filing Date	December 29, 2000
	First Named Inventor	R. A. WIEDEMAN
	Art Unit	2817
	Examiner Name	James D. Ewart
	Attorney Docket Number	YR0-61
Total Number of Pages in This Submission		5


ENCLOSURES (Check all that apply)		
<input type="checkbox"/> Fee Transmittal Form <input type="checkbox"/> Fee Attached <input type="checkbox"/> Amendment/Reply <input type="checkbox"/> After Final <input type="checkbox"/> Affidavits/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input type="checkbox"/> Information Disclosure Statement <input type="checkbox"/> Certified Copy of Priority Document(s) <input type="checkbox"/> Reply to Missing Parts/Incomplete Application <input type="checkbox"/> Reply to Missing Parts under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation <input type="checkbox"/> Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Request for Refund <input type="checkbox"/> CD, Number of CD(s) _____ <input type="checkbox"/> Landscape Table on CD	<input type="checkbox"/> After Allowance Communication to TC <input checked="" type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input checked="" type="checkbox"/> Other Enclosure(s) (please identify below): Cover letter
Remarks		

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name	K&A Associates		
Signature			
Printed name	Kenneth W. Float		
Date	1/7/2008	Reg. No.	29,233

CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature			
Typed or printed name	Kenneth W. Float	Date	1/7/2008

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 36 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

**RECEIVED
CENTRAL FAX CENTER**

JAN 07 2008

**PATENT
YR0-61**

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: R. A. WIEDEMAN ET AL : Date: January 7, 2008
Serial No.: 09/751,765 :
Filed: December 29, 2000 : Group Art Unit: 2617
For: METHOD AND APPARATUS PROVIDING :
SUPPRESSION OF SYSTEM ACCESS BY USE : Examiner: James D. Ewart
OF CONFIDENCE POLYGONS, VOLUMES :
AND SURFACES IN A MOBILE SATELLITE SYSTEM :


COVER LETTER

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Enclosed are three copies of revised page 3 of the Appeal Brief. The "Status of Amendments" section has been corrected to identify the correct date of filing of the response after final rejection. Entry of the revised pages of the Appeal Brief is respectfully requested.

Respectfully submitted,



Kenneth W. Float
Registration No. 29,233

K&A Associates
1407 Foothill Blvd., Suite 233
La Verne, CA 91750
Telephone: (626) 339-6051
Facsimile: (626) 339-6148

Serial No.: 09/751,765..... Page 3

STATUS OF AMENDMENTS

A paper dated August 1, 2007 filed in response to the final rejection made a minor amendment to claim 10.

SUMMARY OF CLAIMED SUBJECT MATTER

The present invention provides that the teachings can be employed to control the actions of a user terminal (UT) (5, Fig. 1) located at a remote location, possibly far from a gateway (GW) (1, Fig. 1), which has an interface to the Public Switched Telephone Network (PSTN) (2, Fig. 1) and/or to the Internet or to any other kind of network, either mobile or fixed. These teachings employ a computer generated and stored database of an area (referred to as a Confidence Polygon) (9, Fig. 1), a volume (referred to as a Confidence Volume) (31, Fig. 2), and/or a plane (referred to as a Confidence Surface) (33, Fig. 2) to establish a geometric shape located on the earth, above the earth or in space, or combinations thereof. In addition, there is assigned to these areas, volumes and/or planes a static or a variable value referred to as a Confidence Limit (CL) that can be compared to a value of an error (E) in a position location (12, Fig. 1) of the UT. The error signal can either be generated by the UT or by the GW. A controller (66, Fig. 6), which may be a part of the GW, acts upon the database of the geometric shapes, and the assigned or derived values of CL and E, to determine if the comparison of CL and E, combined with the current position of the UT, yields a certain result according to the operational mode of the controller. There can be many operational modes of the controller. Depending on the operational mode the result of the comparison of the CL assigned to the area, volume or plane is used to affect control of the UT or an external device attached to the UT. By example, the UT may be forbidden or allowed to access the system or to make or receive a call, or some operational characteristic(s) of the UT may be specified, such as transmitter power, frequency, and the like. The end result, by example, is an ability to provide protection for a site, such as a radio astronomy site from UT emissions.

Also disclosed is a method for operating a mobile satellite communication system having at least one GW (1, Fig. 1), at least one user terminal UT (5, Fig. 1), and a constellation of satellites (4, Fig. 1). The method includes the steps of, for a site to be protected, for example, from UT transmissions, specifying an exclusion or inclusion zone having a confidence limit (CL) associated therewith; and selectively providing service to a UT depending on a determined location of the UT relative to the exclusion or inclusion zone

Serial No.: 09/751,765..... Page 3

STATUS OF AMENDMENTS

A paper dated August 1, 2007 filed in response to the final rejection made a minor amendment to claim 10.

SUMMARY OF CLAIMED SUBJECT MATTER

The present invention provides that the teachings can be employed to control the actions of a user terminal (UT) (5, Fig. 1) located at a remote location, possibly far from a gateway (GW) (1, Fig. 1), which has an interface to the Public Switched Telephone Network (PSTN) (2, Fig. 1) and/or to the Internet or to any other kind of network, either mobile or fixed. These teachings employ a computer generated and stored database of an area (referred to as a Confidence Polygon) (9, Fig. 1), a volume (referred to as a Confidence Volume) (31, Fig. 2), and/or a plane (referred to as a Confidence Surface) (33, Fig. 2) to establish a geometric shape located on the earth, above the earth or in space, or combinations thereof. In addition, there is assigned to these areas, volumes and/or planes a static or a variable value referred to as a Confidence Limit (CL) that can be compared to a value of an error (E) in a position location (12, Fig. 1) of the UT. The error signal can either be generated by the UT or by the GW. A controller (66, Fig. 6), which may be a part of the GW, acts upon the database of the geometric shapes, and the assigned or derived values of CL and E, to determine if the comparison of CL and E, combined with the current position of the UT, yields a certain result according to the operational mode of the controller. There can be many operational modes of the controller. Depending on the operational mode the result of the comparison of the CL assigned to the area, volume or plane is used to affect control of the UT or an external device attached to the UT. By example, the UT may be forbidden or allowed to access the system or to make or receive a call, or some operational characteristic(s) of the UT may be specified, such as transmitter power, frequency, and the like. The end result, by example, is an ability to provide protection for a site, such as a radio astronomy site from UT emissions.

Also disclosed is a method for operating a mobile satellite communication system having at least one GW (1, Fig. 1), at least one user terminal UT (5, Fig. 1), and a constellation of satellites (4, Fig. 1). The method includes the steps of, for a site to be protected, for example, from UT transmissions, specifying an exclusion or inclusion zone having a confidence limit (CL) associated therewith; and selectively providing service to a UT depending on a determined location of the UT relative to the exclusion or inclusion zone

Serial No.: 09/751,765..... Page 3

STATUS OF AMENDMENTS

A paper dated August 1, 2007 filed in response to the final rejection made a minor amendment to claim 10.

SUMMARY OF CLAIMED SUBJECT MATTER

The present invention provides that the teachings can be employed to control the actions of a user terminal (UT) (5, Fig. 1) located at a remote location, possibly far from a gateway (GW) (1, Fig. 1), which has an interface to the Public Switched Telephone Network (PSTN) (2, Fig. 1) and/or to the Internet or to any other kind of network, either mobile or fixed. These teachings employ a computer generated and stored database of an area (referred to as a Confidence Polygon) (9, Fig. 1), a volume (referred to as a Confidence Volume) (31, Fig. 2), and/or a plane (referred to as a Confidence Surface) (33, Fig. 2) to establish a geometric shape located on the earth, above the earth or in space, or combinations thereof. In addition, there is assigned to these areas, volumes and/or planes a static or a variable value referred to as a Confidence Limit (CL) that can be compared to a value of an error (E) in a position location (12, Fig. 1) of the UT. The error signal can either be generated by the UT or by the GW. A controller (66, Fig. 6), which may be a part of the GW, acts upon the database of the geometric shapes, and the assigned or derived values of CL and E, to determine if the comparison of CL and E, combined with the current position of the UT, yields a certain result according to the operational mode of the controller. There can be many operational modes of the controller. Depending on the operational mode the result of the comparison of the CL assigned to the area, volume or plane is used to affect control of the UT or an external device attached to the UT. By example, the UT may be forbidden or allowed to access the system or to make or receive a call, or some operational characteristic(s) of the UT may be specified, such as transmitter power, frequency, and the like. The end result, by example, is an ability to provide protection for a site, such as a radio astronomy site from UT emissions.

Also disclosed is a method for operating a mobile satellite communication system having at least one GW (1, Fig. 1), at least one user terminal UT (5, Fig. 1), and a constellation of satellites (4, Fig. 1). The method includes the steps of, for a site to be protected, for example, from UT transmissions, specifying an exclusion or inclusion zone having a confidence limit (CL) associated therewith; and selectively providing service to a UT depending on a determined location of the UT relative to the exclusion or inclusion zone